



GB04/4994



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ


REC'D 28 DEC 2004	
WIPO	PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed


Dated 13 December 2004

**PRIORITY
DOCUMENT**

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

ST AVAILABLE COPY

Patents Form 1/77

Patents Act 1977
(Rule 16)

1/77

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road

Newport
South Wales26NOV03 E855184 13
P01/7700 0.00-08PT0900

1.	Your Reference	P59069V-GB		
2.	Patent Application number (The Patent Office will fill in this part)	0327492.5		
3.	Full name, address and postcode of the or each applicant (<u>underline all surnames</u>)	UTM IP Limited Hampstead Avenue Mildenhall Suffolk IP28 7AS		
	Patents ADP Number (if you know it)	8614273001		
	If the applicant is a corporate body, give the country/state of its incorporation	United Kingdom		
4.	Title of the invention	Low Energy Training Cartridge		
5.	Name of your agent (if you have one)	FRY HEATH & SPENCE LLP		
	"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)	The Gables Massetts Road Horley Surrey RH6 7DQ United Kingdom		
	Patents ADP Number (if you know it)	05880273001 8459554001		
6.	Priority: Complete this section if you are declaring priority from one or more earlier patent applications filed in the last 12 months.	Country	Priority application number (if you know it)	Date of filing (day / month / year)
7.	Divisionals, etc: Complete this section only if this application is a divisional application or resulted from an entitlement dispute (see note f).	Number of earlier application	Date of filing (day / month / year)	
8.	Is a Patents Form 1/77 (Statement of inventorship and of right to grant of a patent) required in support of this request?	Yes		

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document.

Continuation sheets of this form

Description 8

Claim(s) 3

Abstract 1

Drawing(s) 2 only

10. If you are also filing any of the following, state how many against each item.

Priority documents 0

Translations of priority documents 0

Statement of inventorship and right to grant of a patent (Patents Form 7/77) 0

Request for preliminary examination and search (Patents form 9/77) 1

Request for substantive examination (Patents form 10/77) 0

Any other documents (please specify) 0

11.

I/We request the grant of a patent on the basis of this application.

Signature

Date

26 November 2003

12.

Name and daytime telephone number of person to contact in the United Kingdom

Victoria J Townsend - 01293 776880

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you filing or applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- Part 7 should only be completed when a divisional application is being made under section 15(4), or when an application is being made under sections 8(3), 12(6) and 37(4) following an entitlement dispute. By completing part 7 you are requesting that this application takes the same filing date as an earlier UK application. If you want the new application to have the same priority date(s) as the earlier UK application, you should complete part 6 with the priority details.

DUPLICATE

1

LOW ENERGY TRAINING CARTRIDGE

The present invention relates to ammunition, particularly non-lethal ammunition intended for use in training and war games. The invention has particular application in cartridges in which a rearwards movement of a portion of the cartridge is used to initiate the recycling of an automatic or semi-automatic firearm.

Low energy cartridges for cycling self loading guns are widely known. For example US Pat. 5,677,505, US Pat. 6,095,051, US Pat. 5,700,972 and US Pat. 6,439,123 B1 all relate to a two part cartridge which has a casing slidable relative to a plug at the forward end of the cartridge. When the cartridge is loaded in a gun and fired, force provided by a propellant gas is employed to urge the slidable casing back against the breech-block and recycle the weapon.

An example of such a cartridge is illustrated in Fig.1 of the accompanying drawings. A problem that arises with these prior art cartridges is that they perform inconsistently when used in guns of the same calibre but made by different manufacturers. This is due to design variations between guns of different manufacturers, variations which the manufacturers claim, when used in conjunction with live ammunition, provide certain technical advantages. These variations, discussed in more detail in the description of Figure 1 given below, can result in different degrees of gas loss and volume related pressure variations around the bullet.

The high energy associated with propulsion of live ammunition copes with these differences, however, the much smaller amount of energy available to propel a bullet using prior art, low energy training ammunition cartridges does not cope well. Consequently, varying

propellant gas loss and pressure variations associated with comparable weapons from different manufacturers significantly affects performance when these guns are used with low energy cartridges to an extent that, behaviour of the ammunition when fired from a weapon becomes inconsistent and unpredictable. The changes encountered in the ammunition performance from one gun type/make to another are considered unacceptable.

The present invention aims to provide a novel low energy cartridge which allows more consistent and predictable performance when firing non-lethal ammunition from weapons of the same calibre, but different manufacturer.

In accordance with the present invention there is provided a low energy cartridge comprising:

- an outer casing;

- a rear telescopically slidable portion disposed, in use, to be telescopically extendable with respect to the outer casing in a direction towards the breech-block of a firearm;

- a front telescopically slidable portion disposed, in use, to be telescopically extendable with respect to the outer casing in a direction towards the barrel of a firearm;

- means for causing each telescopically slidable portion, in use, too telescopically extend in reaction to firing of a firearm containing the cartridge;

- an open end of the front portion configured to receive a projectile and

- means for propelling a projectile from the open end.

Optionally the cartridge further includes a projectile received in the front portion of the cartridge, the projectile comprising a bullet which is configured such that, in use, the bullet remains sealed in the front portion

of the cartridge until a portion of it has entered the rifled part of the barrel of the firearm.

Preferably, the means for causing the telescopically slidable portions to telescopically extend include a gas releasing device positioned to the rear of the rear telescopically slidable portion, an open ended gas passage extending through the portion and forwardly of the gas releasing device and a closure member sealingly slidably located in the gas passage. The gas releasing device may be a primer.

Conveniently, the means for causing the portions to telescopically slide comprise a primer positioned towards the rear of each of the front and rear telescopically slidable portions. Optionally, the means may comprise a primer positioned to the rear of the rear portion which in turn ignites a propellant charge causing both portions to telescopically slide. The propellant charge may also, optionally, propel a projectile seated in the gas passage of the front portion. Where a primer is present in the front portion, this primer may be initiated by percussion, for example on impact by the aforementioned closure member or, by chemical action of a component of gas released in the gas passage of the rear portion.

In use of a typical embodiment, the cartridge is loaded in the firearm with both telescopically slidable portions retracted into the outer casing. A projectile is positioned in the open end of the gas passage of the front portion. When the firearm is fired, the firing pin strikes the primer causing release of gas into the gas passage extending forwardly of the primer. As the gas expands, the closure member is caused to slide along the gas passage at increasing speed towards the primer of the second telescopically slidable portion. At the same time, the expanding gas forces the rear telescopically slidable portion to extend towards the breach block of the firearm, travelling in an opposing direction to the closure member. As the closure member exits the open end of the extending rear portion,

gas escapes the passage of the rear portion and expands into a space to the rear of the front portion. This causes the telescopically slidable front portion to extend towards the barrel of the firearm. Thus, the two telescopically slidable portions are caused to travel in opposing directions.

The accelerating closure member strikes the primer of the front portion causing release of a second quantity of gas into the gas passage extending forwardly of this second primer. As it expands, this second quantity of gas forces the projectile out of the open ended gas passage and into the barrel of the firearm.

It will be appreciated that the front telescopically slidable portion extends before the bullet is propelled through the barrel of the firearm. The portion thus creates a seal between the cartridge and the barrel to enable all of the propellant gas, without pressure drops or gas losses, to propel the bullet up the barrel. This overcomes inconsistencies in performance of cartridges in firearms of varying manufacturer's designs.

Desirably, the outer casing is shaped so as to include at or near each end an inwardly jutting surface which serves to stop the telescopically slidable portions separating from the outer casing when they extend. Optionally, the inwardly jutting surface comprises an annular flange having an inner radius which is slightly smaller than the largest radius of the corresponding, telescopically slidable portion.

The closure member is conveniently a plug which has a cross section in a direction perpendicular to the direction of travel of the telescopically slidable portions, of similar shape and size to that of the gas passage of the first telescopically slidable portion. Desirably, the closure member is substantially spherical. The closure member may, optionally, comprise a steel ball. Alternatively, the closure member may comprise a ball of plastic material. The outer surface of the closure member is

desirably selected to be of a low friction material so as to allow the member to easily slide along the gas passage when the first gas is released.

Desirably a gas tight seal is provided between at least the rear telescopically slidable portion and the outer casing and optionally also the front telescopically slidable portion and the outer casing.

Either or both of the primers may in turn ignite a propellant charge.

For the purposes of exemplification, an embodiment of the invention will now be further described with reference to the following Figures in which;

Figure 1 shows schematically a typical cartridge as is known from the prior art, correctly located in the chamber of a firearm.

Figure 2 shows in cross section an embodiment of a telescopically expandable cartridge in accordance with the invention located in the chamber of a firearm, prior to firing;

Figure 3 shows the embodiment of Figure 2 shortly after the firearm has been fired but before the projectile is propelled into the barrel of the firearm;

Figure 4 shows the embodiment of Figure 3 at a later moment when the projectile has been propelled into the barrel of the firearm.

Figure 1 illustrates schematically a typical cartridge Z as is known from the prior art. In the figure, dimension A is a constant used by all firearm manufacturers for a given ammunition type. The cone shaped surface B is not common to all manufacturers designs and may be plane

and smooth. Also, in some manufacturers firearms, the cartridge may make a seal between the rifled barrel X and the chamber Y or it may have grooves that run from the surface with dimension C across the cone shaped face and along the surface with dimension A thereby rendering it impossible to make a seal between the rifled barrel X and the chamber Y.

The dimensions C and D may vary from manufacturer to manufacturer as may diameters E and F. H represents the direction of extension of a telescopically expanding low energy cartridge during recycling.

The dimension I may vary from manufacturer to manufacturer. In addition, manufacturers use slightly varying breech and chamber dimensions and configurations (for example fluted chambers) for use with live ammunition.

The variations in the previously discussed design parameters of firearms of the same calibre but different manufacturer cause gas loss and volume related pressure variations around a bullet propelled from the firearm.

Figure 2 illustrates a cartridge in accordance with the invention. As can be seen from the Figure, the cartridge of the invention comprises an outer casing 4 in to which are telescopically slidably arranged a rear portion 1 and front portion 6. The rear portion includes a primer 2 sited to the rear of the portion where, in use, it can be initiated in striking by a firing pin of the firearm (not shown). At the opposing end of the rear portion 1, on the outer surface of the portion 1 is an annular flange 9 which includes an annular recess which receives a sealing ring 10. The sealing ring 10 provides a gas tight seal which prevents gases released from the primer 2 escaping from the rear of the cartridge. Towards the rear of the outer casing 4 on an inner surface of the casing as an annular

protrusion 8. the inner radius of the annular protrusion is selected to be smaller than the outer radius of the flange 9 such that, when the rear portion 1 extends, it is prevented from separating from the casing by flange 9 abutting against protrusion 8.

A gas passage 11 extends forwardly of the primer 2 in the rear portion 1. Carried within the gas passage 11 is a closure member which may be a steel or plastic ball 3 which has a diameter comparable to that of the diameter of the gas passage 11. The ball 3 acts as a closure member preventing the escape of gas released by the primer 2 from escaping through the open end of the gas passage 11. The ball 3 is, however, slidable within the gas passage 11.

The front portion 6 is made from plastic or composite construction of pliable material which serves to seal in the outer casing 4. The pliable nature of the material allows deformation at the interface between the front portion 6 and the entry to the barrel X maintaining a seal even if fluting is present. The front portion further comprises a second primer 5 sited towards its rear end. A second gas passage 12 extends forwardly of the second primer 5 and opens into a socket 13 configured to receive an end of a bullet or other projectile 7.

As for the rear portion, the smallest diameter (at position 14) of the front end of the casing 4 is smaller than the largest diameter (at position 15) of the front portion 6 so as to prevent separation of the front portion 6 from the casing 4 when the front portion telescopically extends.

In a desirable application of an embodiment of the invention, a bullet 7 is configured such that the bullet 7 remains sealed in the socket 13 of the pliable front portion 6 of the cartridge until it has entered the rifled part X of the barrel of the firearm. This may be achieved by

providing a bullet 7 with a parallel section 7a, sealed in the socket 13 of the pliable front portion 6.

Figure 3 shows the initial action of the cartridge of Figure 2 when the firearm is fired. On firing, a firing pin P strikes the primer 2 in of the rear portion 1 which causes gas to be released into gas passage 11. The pressure of the gas in passage 11 causes ball 3 to travel towards the front portion 6. As the ball begins to exit the gas passage 11, gas escapes past the ball and begins to force the front 6 and rear 1 portions apart. The rear portion 1 extends telescopically towards the breech of the firearm so as to recycle the firearm as is known from the prior art.

As can be seen from Figure 4, the front portion 6 also telescopically extends so as to seal the front pliable portion at the interface between the guns chamber Y and the barrel X and deposit the front end of the projectile 7 into the barrel X of the firearm. The ball 3 strikes the primer 5 of the front portion 6 causing release of gas into gas passage 12. The released gas builds up a pressure behind projectile 7 which ultimately forces the projectile along the barrel X.

CLAIMS

1. A low energy cartridge comprising:
 - an outer casing;
 - a rear telescopically slidable portion disposed, in use, to be telescopically extendable with respect to the outer casing in a direction towards the breech-block of a firearm;
 - a front telescopically slidable portion disposed, in use, to be telescopically extendable with respect to the outer casing in a direction towards the barrel of a firearm;
 - means for causing each telescopically slidable portion, in use, too telescopically extend in reaction to firing of a firearm containing the cartridge;
 - an open end of the front portion configured to receive a projectile and
 - means for propelling a projectile from the open end.
2. A low energy cartridge as claimed in claim 1 wherein the front telescopically extendable portion is made from a plastic, other pliable material or of composite construction so as to seal the front portion into the outer case and chamber of the gun.
3. A low energy cartridge as claimed in claim 1 or claim 2 further including a projectile received in the front portion of cartridge, the projectile comprising a bullet which is configured such that the bullet remains sealed in the front portion of the cartridge until a portion of it has entered the rifled part of the barrel of the firearm.
4. A low energy cartridge as claimed in claim 1,2 or 3 wherein the means for causing the telescopically slidable portions to telescopically extend include a gas releasing device positioned to the rear of the rear telescopically slidable portion, an open ended

gas passage extending through the portion and forwardly of the gas releasing device and a closure member sealingly slidably located in the gas passage.

5. A low energy cartridge as claimed in any of claims 1 to 4 wherein the means for causing the telescopically slidable portions to telescopically extend includes a primer positioned to the rear of the rear portion and an open ended gas passage extending through the portion and forwardly of the primer.
6. A low energy cartridge as claimed in claim 5 further including a propellant charge ignited by the primer and positioned between the front and rear telescopically slidable portions.
7. A low energy cartridge as claimed in claim 4 or 5 further including a primer positioned to the rear of the front portion and an open ended gas passage extending through the front portion and forwardly of the primer, the open ended gas passage being closable by a projectile.
8. A low energy cartridge as claimed in claim 7 as dependent from claim 4 wherein the primer of the front portion is initiated on impact of the closure member with the primer.
9. A low energy cartridge as claimed in any preceding claim wherein the outer casing is shaped so as to include at or near each end an inwardly jutting surface which serves to stop the telescopically slidable portions separating from the outer casing when they extend.
10. A low energy cartridge as claimed in claim 9 wherein the inwardly jutting surface comprises an annular flange having an inner radius

which is slightly smaller than the largest radius of the corresponding telescopically slidable portion.

11. A low energy cartridge as claimed in any of claims 4 to 10 wherein the closure member comprises a plug which has a cross section in a direction perpendicular to the direction of travel of the telescopically slidable portions, of similar shape and size to that of the gas passage of the first telescopically slidable portion.
12. A low energy cartridge as claimed in claim 11 wherein the closure member is substantially spherical.
13. A low energy cartridge as claimed in claim 12 wherein the closure member is a ball.
14. A low energy cartridge as claimed in claim 13 wherein the ball is made from steel.
15. A low energy cartridge as claimed in claim 13 wherein the ball is made from a plastic material.
16. A low energy cartridge as claimed in any of claims 4 to 13 wherein the closure member has an outer surface which is selected to be of a low friction material so as to allow the member to easily slide along the gas passage.
17. A low energy cartridge as claimed in any preceding claim further including at least one gas tight seal between a telescopically slidable portion and the outer casing.
18. A cartridge substantially as described herein and with reference to the accompanying Figures 2 to 4.

ABSTRACT

LOW ENERGY TRAINING CARTRIDGE

A low energy cartridge comprising:

an outer casing 4;

a rear telescopically slidable portion 1 disposed, in use, to be telescopically extendable with respect to the outer casing 4 in a direction towards the breech-block of a firearm;

a front telescopically slidable portion 6 disposed, in use, to be telescopically extendable with respect to the outer casing 4 in a direction towards the barrel X of a firearm;

means 2, 3 for causing each telescopically slidable portion 1, 6 to telescopically extend in reaction to firing of a firearm containing the cartridge;

an open end 13 of the front portion 6 configured to receive a projectile 7 and

means for propelling a projectile 7 from the open end 13.

[Fig 2]

1/2




FIG. 1.




FIG. 2.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record.**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☒ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.